

8 Channels LoRaWAN Home GW RHF2S024

Description

RisingHF 8 Channels LoRaWAN Home gateway RHF2S024 is an easy installation indoor gateway based on LoRaWAN protocol, which is embedded with Semtech's high performance multi-channel transceiver SX1308 and MTK platform.

The Gateway could connect to LoRaWAN Cloud server via Ethernet network or Wifi. The home GW include 3 modes: AP, STA and PPPoE as Router. Only one RJ45 port is provided but with WAN/LAN switch automatically.

The Home GW is targeted to be used in smart hotel, smart building, smart home, indoor smart parking and as a supplement for the industrial outdoor gateway.

Applications

- Smart hotel
- Smart home
- Indoor smart parking
- Smart building
- Indoor application
- Building automation





LoRaWAN Home Gateway

Product Brief

Features

- 27dBm max output power
- High sensitivity with -141dBm@300bps
- Half duplex mode for LoRaWAN communication
- LoRaWAN uplink: 8 normal multi-SF channels (SF7 to SF12,125kHz), 1 single SF high speed data rate channel and 1 GFSK channel
- LoRaWAN downlink: 1 normal channel(125kHz/250kHz/500kHz LoRa configurable or GFSK)
- Communication data rate 292bps~ 50kbps
- Support LoRaWAN Class A/C
- WIFI 2.4GHz, Compatible with WLAN 802.11b/g/n
- AP mode
- Station mode
- PPPoE mode to connect to network
- 1xLoRaWAN Antenna, 1xWIFI Antenna
- LoRaWAN antenna Gain: 0dBi default
- WIFI antenna Gain: 5dBi default
- 10/100M Ethernet, LAN/WAN switch automatically via one RJ45
- Configurable via WIFI or LAN
- LED status for Power/WIFI/LoRaWAN/USB
- DC 12V input
- Indoor use
- Operating frequency bands (Option when order): 434MHz; 470MHz/510MHz, 780MHz; 868MHz; 915MHz,

Contact: support@risinghf.com