

# IES-3424DSFP-2P-PT

24 10/100TX + 4 DualSpeed SFP IEC 61850-3

Managed Ethernet Switch w/ Enhanced Ring & MMS

- Compliant with IEC61850-3 & IEEE1613
- Built-in MMS server based on IEC61850-90-4 switch data modeling for SCADA with monitoring and control
- Enhanced G.8032 ring protection < 20ms for single ring. Supports auto mode, enhanced mode, train mode, multi-VLAN and basic mode; Enhanced G.8032 ring covers multicast packets; MSTP 16MSTI /RSTP ; support MRP ring
- Miss-wiring avoidance & node failure protection
- User friendly UI, including auto topology drawing; Complete CLI
- Support LACP link aggregation, IGMP v3/router port, DHCP server & DHCP Option82; Port based DHCP distribution, Mac based DHCP server, QoS by VLAN, SSH/SSL, HTTPS, INGRESS/EGRESS ACL L2/L3, QinQ
- Protocol based VLAN ; IPv4 Subnet based VLAN
- USB port to backup, restore the configuration file and upgrade firmware



## OVERVIEW

Lantech IES-3424DSFP-2P-PT is a high performance L2+ (Gigabit uplink) switch with 24 10/100/1000T + 4 Dual Speed SFP that complies with IEC 61850-3 & IEEE 1613. It delivers ITU G.8032 enhanced ring recovery less than 20ms in single ring while also supports train ring, enhanced mode, multiple VLAN model with easy configuration.

The built-in MMS server allows SCADA to control & monitor switch for data modeling.

### **Built-in MMS server for IEC61850 data modeling for monitoring and control**

The built-in MMS (Manufacturing Messaging Specification) server can help SCADA to monitor and control switch by data modeling. It covers system, power, port status, network configuration.

### **Miss-wiring avoidance, Repowered auto ring restore, Loop protection**

The IES-3424DSFP-2P-PT also embedded several features for stronger and reliable network protection in an easy and intuitive way. When the pre-set ring configuration failed or looped by miss-wiring, Lantech IES-3424DSFP-2P-PT is able to alert with the LED indicator and disable ring automatically. Node failure protection ensures the switches in a ring to survive after power breakout is back. The status can be shown in NMS when each switch is back. This feature prevents the broken ring and keep ring alive without any re-configuration needed. Loop protection is also available to prevent the generation of broadcast storm when a dumb switch is inserted in a closed loop connection.

### **Enhanced G.8032 ring, 16 MSTI MSTP; MRP ring**

Lantech IES-3424DSFP-2P-PT features enhanced G.8032 ring which can be self-healed in less than 20ms for single ring topology protection covering Multicast packets. It also supports various ring topologies that covers double ring, multi-chain (under enhanced ring), train ring, basic ring, multiple-VLAN ring and auto-ring with easy setup. The innovative auto-Ring configurator (auto mode) can calculate owner and neighbor in one step. It supports MSTP that allows spanning tree over VLAN for redundant links with 16 MSTI.

### **DHCP option 82 & Port based, Mac based DHCP, Option66, IPv6 DHCP server**

DHCP server can assign dedicated IP address by MAC or by port (Port based for single switch), it also can assign IP address by port for multiple switches with single DHCP option82 server. For the ending device which need to download file from TFTP server, DHCP Option66 server can offer IP address of TFTP server to DHCP client. Optional basic IPv6 DHCP service can be supported.

### **QoS by VLAN for legacy devices**

QoS by VLAN can allow switch to tag QoS by VLAN regardless the devices acknowledge QoS or not in which greatly enhance the bandwidth management in a network.

### **QinQ and GVRP supported**

It supports the QinQ, GVRP for large VLAN segmentation.

***IGMPv3, GMRP, router port, static multicast forwarding and multicast Ring protection***

The unique multicast protection under enhanced G.8032 ring can offer immediate self-recovery instead of waiting for IGMP table timeout. It also supports IGMPv3, GMRP, router port and static multicast forwarding binding by ports for video surveillance application.

***User friendly GUI, Auto topology drawing***

The user friendly UI, innovative auto topology drawing and topology demo makes IES-3424DSFP-2P-PT much easier to get hands-on. The IES-3424DSFP-2P-PT supports DMI interface that can correspond with DDM SFPs (Digital diagnostic monitor) to display the five parameters in Lantech's UI, including optical output power, input power, temperature, laser bias current and transceiver supply voltage\*\*\*. The TX power/RX power raw data is automatically converted to dB values for installer, making it easier to calculate the fiber distance. The complete CLI enables professional engineer to configure setting by command line.

***Editable configuration file; USB port for configuration upload & download***

The configuration file of Lantech IES-3424DSFP-2P-PT can be exported and edited with word processor for the other switches configuration with ease. The factory reset button can restore the setting back to factory default and built-in watchdog design can automatically reboot the switch when CPU is found dead.

The built-in USB port can have configuration upload & download by USB dongle.

***Event log & message; 2 DI / 2 DO***

In case of event, the IES-3424DSFP-2P-PT is able to send an email to pre-defined addresses as well as SNMP Traps our immediately. It provides 2 DI and 2 DO. When disconnection of the specific port was detected; DO will activate the signal LED to alarm. DI can integrate the sensors for events and DO will trigger the alarm while sending alert information to IP network with email and traps.

***Design with Dual powered input; Relay contact alarm***

Lantech IES-3424DSFP-2P-PT supports dual power inputs from DC9.5~60V, 85~264VAC or 100V~370VDC. Featured with relay contact alarm function, the IES-3424DSFP-2P-PT is able to connect with alarm system in case of power failure or port disconnection. The IES-3424DSFP-2P-PT also provides  $\pm 4000V$  EFT,  $\pm 4000V$  Surge and  $\pm 8000V$  ESD air protection, which can reduce unstable situation caused by power line and Ethernet.

***Industrial hardened design for extended temperature operation***


Lantech IES-3424DSFP-2P-PT features high reliability and robustness withstanding extensive EMI/RFI phenomenon, lighting surge, inductive load switching, high ESD, high fault current environment, environmental vibration and shocks usually found in factory, substation, steel automation, aviation, mining and process control. It is the best solution for Automation, transportation, surveillance, Wireless backhaul, Semi-conductor factory and assembly lines.

Lantech IES-3424DSFP-2P-PT can run under widely operational temperature (-40°C~75°C) in the harsh environment.

## FEATURES & BENEFITS

- **24 10/100TX + 4 Dual Speed SFP (Total 28 Ports Switch)**
- **Back-plane (Switching Fabric): 12.8Gbps**
- **16K MAC address table**
- **Built-in MMS server for SCADA data-modeling with control and monitoring**
  - System info
  - Power
  - Device event report
  - Port status
  - Port statistic
  - Port event report
  - Firmware upgrade
  - Network configuration
- **10KB Jumbo frame**
- **User friendly UI, Auto topology drawing, topology demo, Complete CLI for professional setting**
- **Enhanced G.8032 Ring recovery < 20ms in single ring**
  - Support various ring/chain topologies, including train ring, enhanced ring, basic ring, auto ring & multiple VLAN ring
  - Enhanced G.8032 ring configuration with ease
  - Auto ring configuration(auto mode) for single ring
  - Covers multi-cast and data packets
- **DDM to support SFP diagnostic function\*\*\***
  - Automatically convert the raw data into dB values for TX power/RX power, making it easier to measure the fiber distance
- **Provides EFT protection ±4000 VDC for power line.**
- **Supports ±4000 VDC (Contact) and ±8000 VDC (Air) Ethernet ESD protection**
- **±4000V Surge for signal port**
- **provides 8 priority queues Port base, Tag Base and Type of Service Priority**
- **IEEE 802.1d STP, IEEE 802.1w RSTP,802.1s MSTP VLAN redundancy with 16 MSTI**
- **4K 802.1Q VLAN, Port based VLAN, GVRP, QinQ**
- **Supports IEEE 802.1ab LLDP, Cisco CDP; LLDP info can be viewed via Web/ Console**
- **DHCP server / client / DHCP Option 82 relay / DHCP Option 82 server Port based DHCP server; DHCP Option 66; basic IPv6 DHCP server**
- **Mac based DHCP server to assign IP address that includes dumb switches in DHCP network**
- **Bandwidth Control**
  - Ingress packet filter and egress rate limit
  - Broadcast/multicast packet filter control
- **Relay alarm output system events**
- **Miss-wiring avoidance**
  - LED indicator
- **Node failure protection**
  - Ensure the switches in a ring to survive after power breakout is back
  - The status can be shown in NMS when each switch is back
- **TFTP/HTTP firmware upgrade**
- **Configuration backup and restoration**
  - Supports text configuration file for system quick installation
  - USB port for upload / download configuration by USB dongle
- **System Event Log, SMTP Email alert and SNMP Trap for alarm support; 32 RMON counters**
- **Security**
  - SSL/SSH/INGRESS/EGRESS ACL L2/L3
  - MAC address table: MAC address entries/Filter/MAC-Port binding
  - IP Security: IP address security management to prevent unauthorized intruder.
  - Login Security: IEEE802.1X/RADIUS
  - HTTPS for secure access to the web interface
- **Static multicast forwarding forward reversed IGMP flow with multicast packets binding with ports for IP surveillance application**
- **IGMP router port to assign query in ring for reversed multicast video flow**
- **IGMPv1,v2,v3 with Query mode for multimedia; GMRP**
- **Factory reset button to restore setting to factory default**
- **Watchdog design to auto reboot switch CPU is found dead**
- **Supports DIDO (2 Digital Input / 2 Digital Output)**
- **Supports dual power inputs from DC9.5~60V, 85~264VAC or 100V~370VDC for system**
- **IP30 metal housing with DIN rail and Wall-mount\*\* design**

**DIMENSIONS (unit=mm)**



**SPECIFICATION**

Hardware Specification		Jumbo frame	10KB			
IEEE Standards	IEEE 802.3 10Base-T Ethernet	Connectors	24 10/100TX RJ-45 with auto MDI/MDI-X function			
	IEEE 802.3u 100Base-TX Ethernet		4 100M / 1000M Mini-GBIC : SFP sockets			
	IEEE 802.3ab 1000Base-T Ethernet		RS-232 console: Female DB-9			
	IEEE 802.3z Gigabit Fiber		USB for configuration restore/backup			
	IEEE 802.3x Flow Control Capability		LED	Per unit: Power 1 (Green), Power 2 (Green), Alarm (Red), R.M (Green)		
	ANSI/IEEE 802.3 Auto-negotiation			Link/Activity (Green), Full duplex/collision(Yellow), MINI GBIC (Link/Activity)(Green)		
	IEEE 802.1Q VLAN			Power Supply	Two power sockets for switch system, 9.5-60VDC input	
	IEEE 802.1p Class of Service				IEC320 85-264VAC conversion (-AC model)	
	IEEE 802.1X Access Control				AC/DC 85-264VAC/100V-370VDC conversion (-HV model)	
	IEEE 802.1D Spanning Tree				Power Consumption	Full load: 30W/ Unload: 13W
IEEE 802.1w Rapid Spanning Tree	Relay Alarm	Provides one relay output for port breakdown, power fail and alarm.				
IEEE 802.1s Multiple Spanning Tree		Alarm Relay current carry ability: 1A @ DC24V				
IEEE 802.3ad Link Aggregation Control Protocol (LACP)		DI/DO				2 Digital Input (DI) :
IEEE 802.1AB Link Layer Discovery Protocol (LLDP)						Level 0: -30-2V / Level 1: 10-30V
IEEE 802.1x User Authentication (Radius)			Max. input current:8mA			
Switch Architecture			Back-plane (Switching Fabric): 12.8Gbps			2 Digital Output(DO): Open collector to 40 VDC,
				Transfer Rate		
148,800pps for Fast Ethernet port						
1,488,000pps for Gigabit Ethernet / Gigabit Fiber port						
MAC Address			16K MAC address table			

	200mA		based VLAN
Factory reset button & watch dog design	Factory reset button to restore back to factory default settings. Watch dog design can reboot switch automatically when CPU is found dead	IPv6/v4	Present
Case Dimension	19" Metal case, IP-30; 440mm(W)x325mm(D)x44mm(H)	RSTP/MSTP	Supports IEEE802.1d Spanning Tree and IEEE802.1w Rapid Spanning Tree, IEEE802.1s Multiple Spanning Tree with 16 MSTI
Operating Humidity	5%~95% (Non-condensing)	Quality of Service	The quality of service determined by port, Tag and IPv4 Type of service, IPv4 Differentiated Services Code Points - DSCP
Operating Temperature	Extended temperature : -40°C ~75°C	Class of Service	Support IEEE802.1p class of service, per port provides 8 priority queues
Storage Temperature	-40°C ~85°C	QoS by VLAN	Tagged QoS by VLAN for all devices in the network
EMI & EMS	FCC Class A, CE EN55032, CE EN55024, CE EN61000-4-2, CE EN61000-4-3, CE EN61000-4-4, CE EN61000-4-5, CE EN61000-4-6, CE EN61000-4-8, CE EN61000-6-2, CE EN61000-6-4, CE EN61000-6-5	IP Security	Supports 10 IP addresses that have permission to access the switch management and to prevent unauthorized intruder.
Stability Testing	IEC60068-2-32 (Free fall), IEC60068-2-27 (Shock), IEC60068-2-64 (Vibration)	Login Security	Supports IEEE802.1X Authentication/RADIUS
Railway verification	EN50121-4, EN55022 (EMV), EN50125-3 (environmental conditions)	Port Mirror	Support 3 mirroring types: "RX, TX and Both packet"
Power Automation	IEC 61850-3, IEEE 1613, IEC 60255-5	Network Security	Support 10 IP addresses that have permission to access the switch management and to prevent unauthorized intruder. 802.1X access control for port based and MAC based authentication/MAC-Port binding Ingress/Egress ACL L2/L3 SSL/ SSH for Management HTTPS for secure access to the web interface for Authentication
MTBF	511,958 Hrs (standards: IEC 62830)	IGMP	Support IGMP snooping v1,v2,v3; 1024 multicast groups; IGMP router port ; IGMP query; GMRP
Warranty	5 years	Static MAC-Port bridge	Static multicast forwarding forward reversed IGMP flow with multicast packets binding with ports for IP surveillance application
<b>Software Specification</b>		Bandwidth Control	Support ingress packet filter and egress packet limit. The egress rate control supports all of packet type. Ingress filter packet type combination rules are Broadcast/Multicast/Flooded Unicast packet, Broadcast/Multicast packet, Broadcast packet only and all types of packet. The packet filter rate can be set an accurate value through the pull-down menu for the ingress packet filter and the egress packet limit.
Management	SNMP v1 v2c, v3/ Web/Telnet/CLI Management	Flow Control	Support Flow Control for Full-duplex and Back Pressure for Half-duplex
SNMP MIB	RFC 1213 MIBII RFC 1158 MIBII RFC 1157 SNMP MIB, RFC 1493 Bridge MIB, RFC 1573 IF MIB Partial RFC 1643 EtherLike, Partial RFC 1757 RMON, RFC 2674 Q-Bridge MIB RFC 2790 Host Resource MIB LLDP MIB* Private MIB	System Log	Support System log record and remote system log server
ITU G.8032	Support ITU G.8032 for Ring protection in less than 20ms for self-heal recovery (incl. multicast packets) Support various ring/chain topology IES Includes multi-ring & multi-VLAN ring* Enhanced G.8032 ring configuration with ease Ring covers multicast on different ports	SMTP	Supports SMTP Server and 8 e-mail accounts for receiving event alert
MMS Data Modeling	<ul style="list-style-type: none"> <li>● System info</li> <li>● Power</li> <li>● Device event report</li> <li>● Port status</li> <li>● Port statistic</li> <li>● Port event report</li> <li>● Firmware upgrade</li> <li>● Network configuration</li> </ul>	Relay Alarm	Provides one relay output for port breakdown, power fail and alarm. Alarm Relay current carry ability: 1A @ DC24V
User friendly UI	<ul style="list-style-type: none"> <li>■ Auto topology drawing</li> <li>■ Topology demo</li> <li>■ DDM threshold monitoring with dB values***</li> <li>■ Complete CLI for professional setting</li> </ul>	Protection	<ul style="list-style-type: none"> <li>■ Miss-wiring avoidance</li> <li>■ Node failure protection</li> <li>■ Loop protection</li> </ul>
Port Trunk with LACP	LACP Port Trunk: 8 Trunk groups	SNMP Trap	Up to 10 trap stations; trap types including: <ul style="list-style-type: none"> <li>● Device cold start</li> <li>● Authorization failure</li> <li>● Port link up/link down</li> <li>● DI/DO open/close</li> <li>● Typology change(ITU ring)</li> <li>● Power failure</li> <li>● Environmental abnormal**</li> </ul>
LLDP	Supports LLDP to allow switch to advise its identification and capability on the LAN	DHCP	Provide DHCP Client/ DHCP Server/DHCP Option 82 relay/ server
CDP	Cisco Discovery Protocol for topology mapping	Mac based DHCP Server	Assign IP address by Mac that can include dumb switch in DHCP network
VLAN	Port Based VLAN IEEE 802.1Q Tag VLAN (256 entries)/ VLAN ID (Up to 4K, VLAN ID can be assigned from 1 to 4096.) GVRP, QinQ, Protocol based VLAN ; IPv4 Subnet	DNS	Provide DNS client feature and support Primary and Secondary DNS server.
		SNTP	Supports SNTP to synchronize system clock in Internet
		Firmware Update	Supports TFTP firmware update, TFTP backup and restore; HTTP firmware upgrade
		Configuration	Supports text configuration file for system quick

backup & restore installation  
USB port to upload/download firmware by USB  
dongle

\*\*Optional  
\*\*\*Optional DDM SFP required

\*Future Release

## ORDERING INFORMATION

- **IES-3424DSFP-2P-PT.....P/N: 8388-506**  
24 10/100TX + 4 Dual SFP IEC61850-3 Managed Ethernet Switch w/ Enhanced Ring & MMS, w/ One isolated DC 9.5-60VDC power supply + 1x additional power socket; -40°C to 75°C
- **IES-3424DSFP-2P-PT-HV.....P/N: 8388-508**  
24 10/100TX + 4 Dual SFP IEC61850-3 Managed Ethernet Switch w/ Enhanced Ring & MMS, w/ One isolated AC/DC 85-264VAC/100V-370VDC power conversion + 1x additional power socket; -40°C to 75°C
- **IES-3424DSFP-2P-PT-AC.....P/N: 8388-510**  
24 10/100TX + 4 Dual SFP IEC61850-3 Managed Ethernet Switch w/ Enhanced Ring & MMS, w/ One isolated 90-305VAC/120-430VDC power supply; -40°C to 75°C + 1 x additional power socket; -40°C to 75°C

## OPTIONAL ACCESSORIES

### Power

#### EOTH000701

Isolation Power 85-264VAC, 100-370VDC 1.5A , 47-63HZ



#### EOTH000702

Isolation Power 36-75VDC, 2.5A



#### EOTH000703

Power 85-264VAC IEC320 socket, 1.5A , 47-63HZ



#### EOTH000704

Power Input Module 9.5-60VDC, 2.5A



### DIN Rail Power

- **MDR-40 Series** 40W Single Output Industrial Din Rail Power; 85-264VAC / 120-370VDC Input Range; Cooling by free air convection; RoHS2 ; Operating Temp. -20°C-70°C (ambient, derating each output at 4% per degree from 60°C ~ 70°C)
- **MDR-20 Series** 20W Single Output Industrial Din Rail Power; 85-264VAC / 120-370VDC Input Range; Cooling by free air convection; RoHS2 ; Operating Temp. -20°C-70°C (ambient, derating each output at 2.5% per degree from 50°C ~ 70°C)

### Mini GBIC (SFP)

- **8330-162X** MINI GBIC 1000SX (LC/MM/0.5KM) Transceiver
- **8330-163X** MINI GBIC 1000SX2 (LC/MM/2KM) Transceiver
- **8330-165X** MINI GBIC 1000LX (LC/SM/10KM) Transceiver
- **8340-0591** MINI GBIC 1000LHX (LC/SM/40KM) Transceiver

- |                   |  |                   |   |
|-------------------|--|-------------------|---|
| ■ <b>8330-166</b> | MINI GBIC 1000XD (LC/SM/50KM) Transceiver      | ■ <b>8330-182</b> | 1.25Gbps BiDi SFP 40KM Transceiver (WDM 1550) |
| ■ <b>8330-169</b> | MINI GBIC 1000XD (LC/SM/60KM) Transceiver      | ■ <b>8330-181</b> | 1.25Gbps BiDi SFP 60KM Transceiver (WDM 1310) |
| ■ <b>8330-167</b> | MINI GBIC 1000ZX (LC/SM/80KM) Transceiver      | ■ <b>8330-183</b> | 1.25Gbps BiDi SFP 60KM Transceiver (WDM 1550) |
| ■ <b>8330-170</b> | MINI GBIC 1000EZ (LC/SM/120KM) Transceiver     | ■ <b>8330-184</b> | 1.25Gbps BiDi SFP 80KM Transceiver (WDM 1490) |
| ■ <b>8330-168</b> | MINI GBIC 10/100/1000T (100m) Transceiver      | ■ <b>8330-185</b> | 1.25Gbps BiDi SFP 80KM Transceiver (WDM 1550) |
| ■ <b>8330-060</b> | MINI GBIC 100Base (LC/MM/2KM) Transceiver      | ■ <b>8330-071</b> | 125Mbps BiDi SFP 2KM (WDM 1310) Transceiver   |
| ■ <b>8330-065</b> | MINI GBIC 100Base (LC/MM/5KM) Transceiver      | ■ <b>8330-072</b> | 125Mbps BiDi SFP 2KM (WDM 1550) Transceiver   |
| ■ <b>8330-061</b> | MINI GBIC 100Base (LC/SM/30KM) Transceiver     | ■ <b>8330-069</b> | 125Mbps BiDi SFP 20KM (WDM 1310) Transceiver  |
| ■ <b>8330-197</b> | 1.25Gbps BiDi SFP 0.5KM Transceiver (WDM 1310) | ■ <b>8330-068</b> | 125Mbps BiDi SFP 20KM (WDM 1550) Transceiver  |
| ■ <b>8330-198</b> | 1.25Gbps BiDi SFP 0.5KM Transceiver (WDM 1550) | ■ <b>8330-080</b> | 125Mbps BiDi SFP 40KM (WDM 1310) Transceiver  |
| ■ <b>8330-195</b> | 1.25Gbps BiDi SFP 2KM Transceiver (WDM 1310)   | ■ <b>8330-082</b> | 125Mbps BiDi SFP 40KM (WDM 1550) Transceiver  |
| ■ <b>8330-196</b> | 1.25Gbps BiDi SFP 2KM Transceiver (WDM 1550)   | ■ <b>8330-081</b> | 125Mbps BiDi SFP 60KM (WDM 1310) Transceiver  |
| ■ <b>8330-188</b> | 1.25Gbps BiDi SFP 10KM Transceiver (WDM 1310)  | ■ <b>8330-083</b> | 125Mbps BiDi SFP 60KM (WDM 1550) Transceiver  |
| ■ <b>8330-189</b> | 1.25Gbps BiDi SFP 10KM Transceiver (WDM 1550)  | ■ <b>8330-084</b> | 125Mbps BiDi SFP 80KM (WDM 1310) Transceiver  |
| ■ <b>8330-186</b> | 1.25Gbps BiDi SFP 20KM Transceiver (WDM1310)   | ■ <b>8330-085</b> | 125Mbps BiDi SFP 80KM (WDM 1550) Transceiver  |
| ■ <b>8330-187</b> | 1.25Gbps BiDi SFP 20KM Transceiver (WDM 1550)  | ■ <b>8330-191</b> | Dual Speed SFP 100M/1000M-LX 10KM Transceiver |
| ■ <b>8330-180</b> | 1.25Gbps BiDi SFP 40KM Transceiver (WDM 1310)  |                   | All SFP# ended with D are with DDM function   |

**Lantech Communications Global Inc.**

[www.lantechcom.tw](http://www.lantechcom.tw)  
[info@lantechcom.tw](mailto:info@lantechcom.tw)

© 2020 Copyright Lantech Communications Global Inc. all rights reserved.  
The revise authority rights of product specifications belong to Lantech Communications Global Inc.  
Lantech may make changes to specification and product descriptions at anytime, without notice.